

BARITON+[®]

High-Range Water-Reducing Concrete Admixture



RAMKA
CONSTRUCTION
CHEMICALS

BARITON+[®] is a high-range water-reducing admixture for lowering the water-to-cement ratio and producing high-strength concrete. Its extended slump-retention capability is intended for concrete production in hot weather and for reducing workability loss before delivery to the job site.

Guideline for Use

Use BARITON+ only at the batching plant. Its slump-retaining polycarboxylate components are designed for gradual adsorption on cement particles during transport, retaining workability as hydration advances. Controlled batching-plant addition is recommended to avoid problems associated with manual or delayed job-site addition.

Applications

- High-strength concrete production at the batching plant
- Long-distance transport in hot weather
- Self-compacting, fibre-reinforced and high-strength concrete
- Prolonged concrete placements
- Thin, heavily reinforced sections
- Increasing 3-day, 7-day and 28-day strength
- Concrete made with crushed aggregates
- Placement in slabs, foundations, columns, walls and bridges

Approvals / Standards

- ASTM C1017 Type II
- ASTM C494 Type G
- ACI 212.3R-16
- INSO 2930

Advantages / Benefits

- High effectiveness and reduced dosage
- Extended workability and high slump retention
- Easier pumping and reduced equipment wear
- Reduced permeability
- Compatibility with different cement types and supplementary cementitious materials
- Slump retention without a stated delay in compressive-strength development
- Reduced risk of cold joints during prolonged placement

Dosage

0.2 to 0.9% by weight of cement. Depending on the concrete mix design, increasing the dosage may provide greater water reduction, higher flowability and longer slump retention.

Storage

+10°C to +30°C, in dry conditions and away from direct sunlight

Packaging

20 kg can / 1,100 kg tank

Shelf Life

One year from production in the original packaging

Basis Of Data

Product Information

Chemical base	Polycarboxylate ether
Physical state / color	Liquid / translucent amber
Density	1.11 ± 0.05 g/cm ³
pH	3-6
Chloride ion content	None



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.