



DELCO® is a liquid set-retarding admixture formulated to delay concrete setting. The approved source states that its polar molecules delay calcium-ion saturation and the reaction with water, thereby extending the concrete setting time.

Applications

- Mass and semi-mass concrete placements
- Pumpable and vibratable concrete
- Concrete transported over long distances

Approvals / Standards

- ASTM C494 Type B
- EN 934
- INSO 2930

Advantages / Benefits

- Easier concrete placement in windy areas
- Easier transport over long distances
- Improved concrete vibration
- Reduced risk of cold joints in large placements
- Reduced surface cracking
- Compatibility with Portland cements
- Improved long-term concrete strength

Guideline for Use

DELCO may be added at the concrete production station, added to ready-mixed concrete at the job site, or divided between the production station and the job site. For job-site addition, add the measured dosage to concrete brought to the truck-mixer opening and mix for several minutes. Where the dosage is divided between two locations, calculate each portion specifically for the project conditions.

Dosage

The approved source states a dosage range of 0.1 to 0.3 of the cement weight; no percentage symbol is shown. The exact dosage may vary according to air temperature, concrete temperature, cement content and the required setting delay.

Storage

+10°C to +30°C, in dry conditions and away from direct sunlight

Packaging

20 kg can

Shelf Life

One year from production in the original packaging

Health and Safety

- Do not swallow and avoid contact with the eyes.
- In case of accidental skin or eye contact, rinse immediately with plenty of fresh water.
- If swallowed, seek medical attention immediately.
- Refer to the Safety Data Sheet (MSDS).
- Non-flammable.

Basis Of Data

Product Information

Density	$1.1 \pm 0.05 \text{ g/cm}^3$
Chloride ion content	None



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.