

INDEX[®]

Water-Reducing Concrete Admixture



RAMKA
CONSTRUCTION
CHEMICALS

INDEX[®] is a water-reducing concrete admixture for increasing slump and flowability in hot-weather conditions while delaying concrete setting. It gives the concrete a plastic consistency, facilitates pumping and helps limit bleeding and segregation.

Applications

- Pumping concrete through long pipelines
- Increasing slump and flowability at the job site
- Extended slump retention during summer
- Concrete made with rapid-setting cements
- Reducing cold-joint risk during prolonged placement
- Exposed concrete requiring smooth surfaces
- Concrete made with highly absorptive aggregates

Approvals / Standards

- ASTM C1017 Type II
- ASTM C494 Type D
- ACI 212.3R-16
- INSO 2930

Advantages / Benefits

- Improved concrete slump and workability
- Retention of flowability and slump during the first hour of summer placement
- Reduced bleeding and segregation
- Reduced permeability
- Improved durability and strength
- Easier pumping through long pump lines
- Reduced pump wear costs
- Economical mix-design potential
- Reduced surface cracking
- Improved cohesion in poorly graded concrete

Guideline for Use

For job-site addition, visually assess the concrete flowability, bring the concrete to the truck-mixer opening and add INDEX directly onto the concrete while avoiding the drum walls. Return the load to the drum and mix at high speed for 5 minutes. Recheck flowability and discharge when accepted; otherwise repeat the approved procedure.

Dosage

0.5 to 1.5% by weight of cement. The exact dosage is selected according to project conditions.

Storage

+10°C to +30°C, in dry conditions and away from direct sunlight

Packaging

20 kg can / 1,100 kg tank

Shelf Life

One year from production in the original packaging

Health and Safety

- Keep in closed containers away from direct sunlight.
- Do not swallow and avoid contact with the eyes.
- In case of accidental skin or eye contact, rinse immediately with plenty of fresh water.
- If swallowed, seek medical attention immediately.
- Refer to the Safety Data Sheet (MSDS).
- Non-flammable.

Basis Of Data

Product Information

Chemical base	Calcium lignosulfonate
Physical state / color	Liquid / brown
Density	$1.12 \pm 0.05 \text{ g/cm}^3$
pH	7 ± 2
Chloride ion content	None



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.