



LICO[®] is a brown liquid concrete retarder. After addition to concrete, its polar molecules delay saturation of calcium ions in the aqueous phase, thereby delaying cement hydration and concrete setting.

Applications

- Mass concrete placements
- Semi-mass concrete placements
- Production of concrete with suitable pumpability

Approvals / Standards

- ASTM C494M Type B
- EN 934
- INSO 2930

Advantages / Benefits

- Facilitates concreting in hot and windy regions
- Enables concrete transport over long distances
- Improves concrete response to vibration
- Helps prevent cold joints in large-area placements
- Helps prevent surface cracking
- Compatible with Portland cements
- Improves long-term concrete strength

Guideline for Use

LICO may be mixed with part of the mixing water before addition, added to the prepared concrete and mixed before placement, or introduced at the batching plant or into the truck mixer for ready-mixed concrete. Dose accurately in accordance with the product label.

Dosage

The average dosage varies from 0.1 to 0.3% by weight of cement, depending on air temperature, concrete temperature, cement content and the required setting delay. Determine the exact dosage through laboratory trials.

Storage

+10°C to +30°C; store in dry conditions away from direct sunlight.

Packaging

20 kg plastic can

Shelf Life

1 year from the date of production in the original packaging.

Health and Safety

- Do not swallow and avoid contact with the eyes.
- In case of accidental contact with the skin or eyes, rinse immediately with plenty of fresh water.
- If swallowed, seek immediate medical attention.
- Refer to the Material Safety Data Sheet (MSDS).
- Non-flammable.

Basis Of Data

Product Information

density	1.1±0.05 g/cm ³
chloride_ion	None



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.