

MAYA®

Concrete Mold Release Agent



RAMKA
CONSTRUCTION
CHEMICALS

MAYA® is an amber liquid mould-release agent that facilitates separation of concrete from formwork and helps prevent concrete-surface discoloration. It improves the final surface quality and is commonly used for precast products and forms for elements that will subsequently receive cementitious finishing or coatings.

Applications

- Coating metal, timber, plastic, fiberglass and other forms before concrete placement
- Coating formwork for concrete sections

Advantages / Benefits

- Facilitates the release of air bubbles adjacent to the form
- Facilitates demoulding
- Helps prevent contamination, staining and discoloration of concrete surfaces
- Provides suitable coverage of the form surface
- Helps prevent formwork corrosion
- Prevents bonding between concrete and formwork

Guideline for Use

Apply MAYA by paintbrush, brush, roller or spray gun. Do not add water. Where dilution is required under special conditions, use a petroleum solvent such as diesel fuel only after consulting RAMKA technical specialists regarding the correct solvent dosage.

Dosage

1 L for 10 to 12 m² of form surface. Actual consumption depends on form type and site environmental conditions.

Storage

+10°C to +30°C; store in dry conditions away from direct sunlight.

Packaging

15 kg plastic can

Shelf Life

1 year from the date of production in the original packaging.

Health and Safety

- Do not swallow and avoid contact with the eyes.
- In case of accidental contact with the skin or eyes, rinse immediately with plenty of fresh water.
- If swallowed, seek immediate medical attention.
- Refer to the Material Safety Data Sheet (MSDS).
- Non-flammable.

Basis Of Data

Product Information

density	0.85±0.05 g/cm ³
---------	-----------------------------



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.