

METRON[®]

High-Range Water-Reducing Concrete Admixture



RAMKA
CONSTRUCTION
CHEMICALS

METRON[®] is a slump-retaining polycarboxylate-ether admixture for reducing the water-to-cement ratio and producing high-strength concrete. The approved source states that it initially increases flowability in a controlled manner and may continue increasing slump for up to 2 hours after loading into the truck mixer, depending on dosage, thereby limiting workability loss in hot weather.

Guideline for Use

Use METRON at the concrete production plant. Its delayed-action polycarboxylate mechanism is intended to retain flowability during transport. The approved source recommends batching-plant addition under controlled mixing conditions and advises against manual or delayed addition at the job site.

Dosage

0.6 to 1.6% by weight of cement. Depending on the concrete mix design, a higher dosage may provide longer slump retention.

Applications

- High-strength concrete production at the batching plant
- Transport in hot weather for up to 2 hours without slump loss
- Large-volume or prolonged concrete placements
- Increasing 3-day, 7-day and 28-day strength
- Reducing cement content and optimising the concrete mix design
- Placement in slabs, foundations, columns, walls and bridges

Approvals / Standards

- ASTM C1017 Type II
- ASTM C494 Type G
- ACI 212.3R-16
- INSO 2930

Advantages / Benefits

- High slump-retention capacity
- Extended concrete workability
- Easier pumping and reduced equipment wear
- Improved concrete cohesion and viscosity
- Reduced permeability
- Slump retention without a stated delay in compressive-strength development
- Reduced risk of cold joints during prolonged placement

Product Data Sheet

METRON[®] CONCRETE POWER PLASTICIZER SERIES

July 2026, Version 2.00

Storage

+10°C to +30°C, in dry conditions and away from direct sunlight

Packaging

20 kg can / 1,100 kg tank

Shelf Life

One year from production in the original packaging

Health and Safety

- Do not swallow and avoid contact with the eyes.
- In case of accidental skin or eye contact, rinse immediately with plenty of fresh water.
- Non-flammable.

Basis Of Data

Product Information

Chemical base	Polycarboxylate ether
Physical state / color	Liquid / colorless and translucent
Density	1.10 ± 0.05 g/cm ³
pH	3-7
Chloride ion content	None



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.