

# REPAIR<sup>®</sup>

Concrete Repair



**RAMKA**  
CONSTRUCTION  
CHEMICALS

**REPAIR<sup>®</sup>** powdered concrete repair mortar is a ready-to-use repair product with high workability and strong adhesion. It covers concrete surfaces uniformly and reduces surface permeability. It is used to repair and level surfaces and to fill voids, cracks, and holes around bolts. Quality polymer resins in its formulation improve its waterproofing properties, making it suitable for waterproofing repair work.

## Guideline for Use

Surface preparation: remove all dust and contamination. Add water slowly to the repair material and mix with an electric mixer until a uniform mortar is obtained, then dampen the substrate. Application: for local repairs, apply a suitable amount of prepared mortar to the damp surface with a trowel. For extensive repairs, use screed guides; when the repair thickness exceeds 2 cm, build up the prepared mortar gradually. Curing: keep the surface moist by spraying for at least one full day (24 hours).

## Applications

- Filling cracks and joints in concrete.
- Smoothing and levelling concrete surfaces.
- Reducing concrete-surface permeability.
- Preparing walls and floors to provide a uniform surface before painting.
- Repairing exterior building surfaces.
- Repairing surfaces exposed to water.

## Approvals / Standards

- ASTM C928
- ASTM C1583
- BS EN 12636
- BS EN 12637

## Advantages / Benefits

- Exceptional adhesion that provides a strong bond between different concrete surfaces and supports long-term integrity of repaired or reconstructed areas.
- Compatible with a range of construction materials, including reinforcement and steel bars, for minor defects and wider surface repairs.
- Creates a uniform surface, masks surface irregularities, and provides resistance to environmental exposure and freeze-thaw cycles.
- Reduces surface permeability by forming a protective layer against moisture ingress and water-related damage.
- Quality polymer resins improve adhesion and waterproofing performance, providing an effective barrier against water-related problems.

## Product Data Sheet

**REPAIR<sup>®</sup> CONCRETE REPAIR SERIES**

July 2026, Version 2.00

**Storage**

+10 to +30 °C; keep away from moisture and direct sunlight.

**Packaging**

25 kg bag

**Shelf Life**

One year in the original packaging.

**Health and Safety**

- This material is not hazardous to human health or the environment, but it must not be swallowed or allowed to contact the eyes.
- In case of accidental contact with skin or eyes, immediately rinse the affected area with plenty of fresh water.
- If swallowed, seek medical attention immediately.
- Refer to the Material Safety Data Sheet (MSDS).
- This material is non-flammable.

**Basis Of Data**

**Product Information**

|               |                         |
|---------------|-------------------------|
| chemical_base | Cement-based mortar     |
| density       | 2/3±1 g/cm <sup>3</sup> |
| chloride_ion  | None                    |



# RAMKA

**CONSTRUCCION CHEMICALS**

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

[www.RamkaCo.com](http://www.RamkaCo.com)

**Important Notes:** The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.