

SEALEX[®]

Surface Sealant



RAMKA
CONSTRUCTION
CHEMICALS

SEALEX[®] polymer waterproofing mortar is a two-component waterproof coating with very high flexibility and long service life. It provides a very high level of impermeability and helps prevent cracking of the applied coating. Made from polymer-cement powder and styrene-acrylic adhesive, it has suitable resistance to freezing and damp conditions.

Applications

- Waterproofing surfaces in water and wastewater treatment plants.
- Waterproofing concrete tanks.
- Eliminating dampness in bathrooms and basements.
- Making concrete and cementitious surfaces impermeable.

Approvals / Standards

- ASTM D412
- ASTM D624
- ASTM D1149
- ASTM C836

Advantages / Benefits

- Suitable waterproofing for frequently used sections.
- Protects concrete surfaces against chloride ions.
- High adhesion to concrete surfaces.
- High flexibility.
- Resistance to freezing.
- Suitable resistance to gasoline, chlorides, and de-icing salts.
- Suitable strength against alkaline materials.

Guideline for Use

For application with fiberglass mesh: grind the substrate until it is free of irregularities; pre-wet the concrete surface; mix the powder and adhesive with an electric mixer at a 2.5:1 ratio; apply the waterproofing mortar to the concrete with a trowel; embed the fiberglass mesh in the applied layer and apply another layer in the same manner; prepare a new powder-to-adhesive mix at a 1:1 ratio and apply the final layer with a brush in perpendicular directions. If tile or ceramic is to be installed over the waterproofed surface, broadcast silica onto the wet final surface to provide the required mechanical key for the tile or ceramic bedding mortar.

Dosage

The average consumption of SEALEX polymer waterproofing mortar is 2 to 5 kg per square metre. The exact consumption must be determined according to project conditions through site trials.

Storage

+5 to +30 °C; keep away from moisture and direct sunlight.

Packaging

10 L pail / 25 kg bag

Shelf Life

One year from the production date in the original packaging.

Health and Safety

- This material is not hazardous to human health or the environment, but it must not be swallowed or allowed to contact the eyes.
- In case of accidental contact with skin or eyes, immediately rinse the affected area with plenty of fresh water.
- If swallowed, seek medical attention immediately.
- Refer to the Material Safety Data Sheet (MSDS).
- This material is non-flammable.



RAMKA

CONSTRUCCION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1th Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.