



FINE[®] is a grey fine cementitious grout powder that hardens rapidly after placement and develops the stated required strength. Its controlled expansion fills voids, gaps and recesses without the stated cracking or shrinkage after hardening. It is a cement-based ready-mix material with stated resistance to high temperatures.

Applications

- Filling voids beneath column base plates
- Foundations for heavy machinery
- Fixing precast columns
- Filling voids around reinforcement and anchor bolts
- Filling cracks and recesses

Approvals / Standards

- ASTM C94
- BS EN 934-6
- BS EN 934-2
- ASTM C348

Advantages / Benefits

- Suitable stability and resistance under static loads
- No cracking after hardening
- Controlled expansion
- Rapid hardening after placement
- High early strength
- Earlier commissioning of the structure
- Easy mixing with water
- Suitable slump and flow

Guideline for Use

For base plates, verify alignment and dimensions. The supporting concrete must be at least 7 days old, and the gap below the plate must be at least 10 mm. Remove dust, oil and rust; saturate the foundation concrete with clean potable water; use watertight, non-absorptive forms extending 2 to 5 cm above the base plate. Pour FINE from one side only. High-density polystyrene sheets may facilitate form movement. Apply at 5°C to 25°C. Do not add other concrete admixtures. Use the prepared grout within 30 minutes and maintain moisture for 7 days away from direct sunlight.

Dosage

Calculate the required quantity from the volume of the placement area and the approved product density. Mix each 1 kg with 100 to 130 cc of water.

Storage

Store away from moisture and direct sunlight.

Packaging

25 kg bag

Shelf Life

1 year from the date of production in the original packaging.

Health and Safety

- Do not swallow and avoid contact with the eyes.
- In case of accidental contact with the skin or eyes, rinse immediately with plenty of fresh water.
- If swallowed, seek immediate medical attention.
- Refer to the Material Safety Data Sheet (MSDS).
- Non-flammable.

Basis Of Data

Product Information

density	2.3±0.1 g/cm ³
Chloride ion	None



RAMKA

CONSTRUCTION CHEMICALS

Tel: (+98)2533557596

Mail : info@Ramkaco.com

1st Floor, Loghman St., Qom, Iran

www.RamkaCo.com

Important Notes: The information, and, in particular, the recommendations relating to the application and end-use of RAMKA products, are given in good faith based on RAMKA's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with RAMKA's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. RAMKA reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.